Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

SECTION 1. IDENTIFICATION

Product name : Modified Hydrofluoric Acid - 85%

Number : 00000011270

Product Use Description : Alkylation catalyst

Note : For additional information, please visit http://www.HFacid.com

(available 24 hours/day, 7days/week).

Manufacturer or supplier's

details

Honeywell International Inc.

115 Tabor Road

Morris Plains, NJ 07950-2546

For more information call : 1-800-622-5002

+1-973-455-6300

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : Medical: 1-800-498-5701 or +1-303-389-1414

Transportation (CHEMTREC): 1-800-424-9300 or +1-703-

527-3887

:

(24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : Colourless fuming liquid

Odor : strong pungent

Classification of the substance or mixture

Classification of the : Corrosive to metals, Category 1 substance or mixture : Acute toxicity, Category 2, Oral

Acute toxicity, Category 2, Inhalation Acute toxicity, Category 1, Dermal Skin corrosion, Category 1A Serious eye damage, Category 1

Page 1 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

GHS Label elements, including precautionary statements

Symbol(s) :





Signal word : Danger

Hazard statements : May be corrosive to metals.

Fatal if swallowed, in contact with skin or if inhaled Causes severe skin burns and eye damage.

Precautionary statements : **Prevention**:

Keep only in original container.

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

Do not get in eyes, on skin, or on clothing. Wash skin thoroughly after handling.

Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Wear protective gloves/ protective clothing.

Wear eye protection/ face protection.

Wear respiratory protection.

Response:

IF SWALLOWED: Immediately call a POISON CENTER/doctor.

IF SWALLOWED: rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a

position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rinsina.

Immediately call a POISON CENTER/doctor.

Remove/Take off immediately all contaminated clothing.

Wash contaminated clothing before reuse. Absorb spillage to prevent material damage.

Storage:

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Keep only in original container.

Disposal:

Dispose of contents/ container to an approved waste disposal

plant.

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

Hazards not otherwise

classified

: Causes severe burns which may not be immediately painful or

visible.

May cause hypocalcemia (depletion of calcium in the body)

which may be fatal.

Specialized medical treatment is required for all exposures.

Carcinogenicity

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, or OSHA.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature : Mixture

Chemical name	CAS-No.	Concentration
Hydrofluoric acid	7664-39-3	85.00 %
Tetrahydrothiophene 1,1-dioxide	126-33-0	15.00 %

SECTION 4. FIRST AID MEASURES

Inhalation : Remove to fresh air. Keep patient warm and at rest. Get

competent medical attention immediately. If breathing has stopped, start artificial respiration at once. An authorized person should administer oxygen to a victim who is having difficulty breathing, until the victim is able to breathe easily by himself. Calcium gluconate, 2.5% in normal saline may be given by nebulizer with oxygen. Do not give stimulants unless instructed to do so by a physician. Victim should be examined by a physician and held under observation for at least 24

hours.

Skin contact : Remove the victim from the contaminated area and

immediately wash the burned area with plenty of water for a minimum of 15 minutes. Limit washing to 5 minutes if treatment specific for HF exposure is available. Remove all contaminated clothing while washing continuously. After thorough washing for at least 5 minutes, the burned area should be immersed in a solution of 0.13% iced aqueous Benzalkonium Chloride until

Page 3 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

pain is relieved. As an alternate first aid treatment, 2.5% calcium gluconate gel may be continuously massaged into the burn area until the pain is relieved. For burns not responsive to topical treatment (as measured by pain being present for longer than 30 minutes) a physician may inject 2.5% - 5% aqueous calcium gluconate beneath, around and in the burned area. Use of local anesthetics is not recommended, as reduction in pain is an indicator of effectiveness of treatment.

Eye contact

Immediately flush the eyes for at least 15 minutes with large amounts of gently flowing water. Hold the eyelids open and away from the eye during irrigation to allow thorough flushing of the eyes. Do not use the benzalkonium chloride (Zephiran) solutions described for skin treatment. If the person is wearing contact lenses, the lenses should be removed, if possible. However, flushing with water should not be interrupted, and the lenses should be removed by a person who is qualified to do so. If sterile 1% calcium gluconate solution is available, water washing may be limited to 5 minutes, after which the 1% calcium gluconate solution should be used to irrigate the eye using a syringe or a continuous irrigation device. Take the victim to a doctor, preferably an eye specialist, as soon as possible. Ice water compresses may be applied to the eyes while transporting the victim to the doctor. If a physician is not immediately available, apply one or two drops of 0.5% tetracaine hydrochloride, 0.5% proparacaine, or other aqueous, topical ophthalmic anesthetic and continue irrigation. Use no other medications unless instructed to do so by a physician. Rubbing of the eyes is to be avoided.

Ingestion

Have the victim drink several large glasses of water or milk to dilute the acid. Do not induce vomiting. Do not give emetics or baking soda. Never give anything by mouth to an unconscious person. Give several glasses of milk or several ounces of milk of magnesia, any calcium containing antacid or grind up and administer up to 30 antacid tablets with water. The calcium or magnesium in these compounds may act as an antidote; however this has not been supported in the literature. Get immediate medical attention. Ingestion of HF is a lifethreatening emergency.

Notes to physician

Indication of immediate medical attention and special treatment needed, if necessary For large skin area burns (totaling greater than 25 square inches), for ingestion and for significant inhalation exposure, severe systemic effects may occur. Monitor and correct for hypocalcemia, cardiac arrhythmias, hypomagnesemia and

Page 4 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

hyperkalemia. In some cases hemodialysis may be indicated. For certain burns, especially of the digits, use of intra-arterial calcium gluconate may be indicated. For inhalation exposures, treat as chemical pneumonia. Monitor for hypocalcemia. 2.5% calcium gluconate in normal saline by nebulizer or by intermittent positive pressure breathing with 100% oxygen may decrease pulmonary damage. Bronchodilators may also be administered. A booklet titled "Recommended Medical Treatment for Hydrofluoric Acid Exposure" is available from the Honeywell HF website: http://www.HFacid.com.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Water spray

Foam

Carbon dioxide (CO2)

Dry chemical

On dilution or dissolving in water, considerable heating always

occurs.

Contact with a relatively small quantity of water creates violent

reaction generating much heat and spattering of hot acid

If use of water is necessary use copious amounts

Specific hazards during

firefighting

: Fire or intense heat may cause violent rupture of packages.

Use a water spray to cool fully closed containers.

Reacts violently with water.

Do not direct water spray at the point of leakage. Contact with metals liberates hydrogen gas.

Hydrogen gas is flammable and may form an explosive

atmosphere.

Diking with silicon materials is to be avoided. May form Silicon

tetrafluoride gas.

In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Sulphur oxides

Gaseous hydrogen fluoride (HF).

Special protective equipment

for firefighters

: Personal protection through wearing a tightly closed chemical

protection suit and a self-contained breathing apparatus.

No unprotected exposed skin areas.

Further information : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment. Use water spray to cool unopened containers.

Page 5 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures Immediately evacuate personnel to safe areas. Immediately contact emergency personnel.

Ensure all affected individuals are in a safe environment. Wear personal protective equipment. Unprotected persons

must be kept away.

Keep people away from and upwind of spill/leak.

Personal protection through wearing a tightly closed chemical protection suit and a self-contained breathing apparatus.

Ensure all equipment (including Personal Protective Equipment

(PPE)) is compatible with Hydrofluoric acid (HF).

Environmental precautions

Prevent further leakage or spillage if safe to do so. Discharge into the environment must be avoided.

Do not flush into surface water or sanitary sewer system. Do not allow run-off from fire fighting to enter drains or water

courses.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Diking with silicon materials is to be avoided. May form Silicon

tetrafluoride gas.

Suppress (knock down) gases/vapours/mists with a water

spray (fog).

Do not direct water spray at the point of leakage. Use water spray cautiously and in large quantities.

With acids neutralization takes place under development of

heat.

Do not pick up with the help of saw-dust or other combustible

substances.

Neutralize acidity with an appropriate alkaline material.

Neutralize with caustics, lime, soda ash, baking soda or other

appropriate alkaline material. Pay attention to the incompatibility statements in Section 10 when effecting

neutralization.

SECTION 7. HANDLING AND STORAGE

Handling

Precautions for safe

Wear personal protective equipment.

handling

Exhaust ventilation at the object is necessary.

Page 6 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

Ensure all equipment (including Personal Protective Equipment

(PPE)) is compatible with Hydrofluoric acid (HF). Perform filling operations only at stations with exhaust

ventilation facilities.

Specialized medical treatment is required for all exposures. Plan first aid action before beginning work with this product. When diluting, add acids to water, never the other way around.

Do not swallow.

Do not breathe vapours or spray mist. Do not get in eyes, on skin, or on clothing.

Advice on protection against fire and explosion

No special precautions required.

Storage

Conditions for safe storage,

including any incompatibilities

Keep containers tightly closed in a cool, well-ventilated place.

Store in a place accessible by authorized persons only.

Store away from incompatible substances.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to

the workstation location.

Plan first aid action before beginning work with this product. Ensure all equipment (including Personal Protective Equipment

(PPE)) is compatible with Hydrofluoric acid (HF).

Engineering measures : Use with local exhaust ventilation.

Apply technical measures to comply with the occupational

exposure limits.

Eye protection : Wear as appropriate:

Goggles or face shield, giving complete protection to eyes

Hand protection : Protective gloves

Gloves must be inspected prior to use.

Replace when worn.

Skin and body protection : Wear suitable protective equipment.

complete suit protecting against chemicals

Respiratory protection : In case of insufficient ventilation wear suitable respiratory

equipment.

Use NIOSH approved respiratory protection.

Have available emergency self-contained breathing apparatus

or full-face airline respirator when using this chemical.

Page 7 / 15

Honeywell

_	_	^	^	_	_	•		0	70
	18	10	10	ш	10	1	17	- J	70
v	v	v	v	v	v	v			ľ

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

Hygiene measures : When using, do not eat, drink or smoke.

Provide adequate ventilation. Keep working clothes separately.

Contaminated work clothing should not be allowed out of the

workplace. Do not swallow.

Do not breathe vapours or spray mist. Do not get in eyes, on skin, or on clothing.

This material has an established AIHA ERPG exposure limit. The current list of ERPG exposure limits can be found at http://www.aiha.org/insideaiha/GuidelineDevelopment/ERPG/D

ocuments/2011erpgweelhandbook_table-only.pdf.

Exposure Guidelines

Exposure Guideiii	163				
Components	CAS-No.	Value	Control	Upda	Basis
			parameters	te	
Hydrofluoric acid	7664-39-3	TWA: Time weighted average	(0.5 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Further : information	Expressed as : as	F			

Hydrofluoric aci	d	7664-39-3	SKIN_DE S : Skin designati on:	Can be absorbed through the skin.	2008	ACGIH:US. ACGIH Threshold Limit Values
Further information		Expressed as : as	F			

Hydrofluoric acid	7664-39-3	Ceiling : Ceiling Limit Value:	(2 ppm)	2008	ACGIH:US. ACGIH Threshold Limit Values
Further : information	Expressed as : as	F			

Hydrofluoric acid	7664-39-3	Conc : Concentr ation:	(30 ppm) NIOSH IDLH (Immediately Dangerous to Life or Health	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
			Concentrations)		

Honeywell

00001127(on 2.5		F	Revision Date	02/13/2018		Print Date 12/26
Hydrofluoric ac	id	7664-39-3	REL: Recomm ended exposure limit (REL):	2.5 mg/m3 (3 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Hydrofluoric ac	id	7664-39-3	Ceil_Tim e: Ceiling Limit Value and Time Period (if specified) :	5 mg/m3 (6 ppm)	2005	NIOSH/GUIDE:US. NIOSH: Pocket Guide to Chemical Hazards
Hydrofluoric acid		7664-39-3	PEL: Permissi ble exposure limit	2.5 mg/m3	02 2006	OSHA_TRANS:US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
Further information	:	Expressed as : a	as F			
Hydrofluoric ac	id	7664-39-3	TWA: Time weighted average	(3 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Further information	:	Expressed as : a	as F			
Hydrofluoric ac	id	7664-39-3	STEL: Short term exposure limit	(6 ppm)	1989	Z1A:US. OSHA Table Z-1-A (29 CFR 1910.1000)
Further information	:	Expressed as : a				1
Hydrofluoric ac	id	7664-39-3	TWA: Time weighted average	(3 ppm)	02 2006	OSHA/Z2:US. OSHA Table Z-2 (29 CFR 1910.1000)

Honeywell

00000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state : Colourless fuming liquid

Odor : strong pungent

pH : Note: Not applicable

Melting point/range : Note: not determined

Boiling point/boiling range : Note: not determined

Flash point : Note: Not applicable

Lower explosion limit : Note: Not applicable

Upper explosion limit : Note: Not applicable

Vapor pressure : 1,079 hPa

at 24 °C(75 °F) 1,733 hPa

at 37.8 °C(100.0 °F)

Vapor density : 2.21 at 21.1 °C

Note: (Air = 1.0)

1.76 at 26.7 °C Note: (Air = 1.0)

Density : 1.0135 g/cm3 at 21.1 °C

Water solubility : Note: completely soluble

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under normal conditions.

Possibility of hazardous

Incompatible materials

reactions

: Hazardous polymerization does not occur.

Conditions to avoid : Heating will cause pressure rise with risk of bursting

: Glass and silicate-containing materials are attacked.
HF contact with glass, concrete and other silicon bearing materials will yield silicon tetrafluoride gas. Pressure buildup from this process has been known to rupture glass containers.
HF contact with carbonates, sulfides and cyanides yield toxic gases such as carbon dioxide, hydrogen sulfide and hydrogen cyanide. Contact with alkalies and some oxides cause strong

violent exothermic reactions. Contact with metals will yield hydrogen gas, a fire and explosive reactive hazard.

On dilution or dissolving in water, considerable heating always

occurs.

When diluting, add acids to water, never the other way

around.

Hazardous decomposition

products

: In case of fire hazardous decomposition products may be

produced such as: Carbon monoxide Carbon dioxide (CO2)

Sulphur oxides

Gaseous hydrogen fluoride (HF).

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : Acute toxicity estimate: 5.88 mg/kg

Method: Calculation method

Acute inhalation toxicity : Acute toxicity estimate: 0.63 mg/l , vapour

Exposure time: 4 h

Method: Calculation method

Acute dermal toxicity : Acute toxicity estimate: 5.88 mg/kg

Method: Calculation method

Page 11 / 15

Honeywell

00000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

Skin irritation

Hydrofluoric acid : Species: Rabbit

Classification: Corrosive

Method: OECD

SECTION 12. ECOLOGICAL INFORMATION

Toxicity to fish

Hydrofluoric acid : LC50: 107.5 mg/l

Exposure time: 96 h

Species: Oncorhynchus mykiss (rainbow trout)

Test substance: Fluoride ion

LC50: 925 mg/l Exposure time: 96 h

Species: Gambusia affinis (Mosquito fish)

Test substance: Fluoride ion

Toxicity to daphnia and other aquatic invertebrates Hydrofluoric acid : EC50: 270 mg/l

Exposure time: 48 h

Species: Daphnia (water flea)
Test substance: Sodium fluoride

Further information on ecology

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental

regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN/ID No. : UN 1052

Proper shipping name : HYDROGEN FLUORIDE, ANHYDROUS

MIXTURE

Poison Inhalation Hazard Hazard zone C

Page 12 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

> Class 8 Packing group I

Hazard Labels 8 (6.1)

IATA UN/ID No. : UN 1052

> Class : 8

> > Not permitted for transport

IMDG UN/ID No. : UN 1052

> Description of the goods : HYDROGEN FLUORIDE, ANHYDROUS

> > **MIXTURE**

Class : 8 Packaging group : 1 Hazard Labels : 8 (6.1) EmS Number : F-C, S-U Marine pollutant : no

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances

Control Act

: On TSCA Inventory

Australia. Industrial

Chemical (Notification and

Assessment) Act

: On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL)

: All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law

List

: On the inventory, or in compliance with the inventory

Korea. Existing Chemicals

: On the inventory, or in compliance with the inventory

Philippines. The Toxic

Inventory (KECI)

Substances and Hazardous and Nuclear Waste Control

Act

: On the inventory, or in compliance with the inventory

Chemical Substances

China. Inventory of Existing: On the inventory, or in compliance with the inventory

Page 13 / 15

Honeywell

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

National regulatory information

US. EPA CERCLA

Hazardous Substances (40

CFR 302)

: The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the

Reportable Quantity (RQ):

Reportable quantity: 100 lbs

Hydrogen fluoride 7664-39-3

SARA 302 Components

: Hydrofluoric acid 7664-39-3

SARA 313 Components

: Hydrofluoric acid 7664-39-3

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

CERCLA Reportable

Quantity

: 118 lbs

California Prop. 65 : This product does not contain any chemicals known to State of

California to cause cancer, birth defects, or any other

reproductive harm.

Massachusetts RTK : Hydrofluoric acid 7664-39-3

Tetrahydrothiophene 1,1-dioxide 126-33-0

New Jersey RTK : Hydrofluoric acid 7664-39-3

: Tetrahydrothiophene 1,1-dioxide 126-33-0

Pennsylvania RTK : Hydrofluoric acid 7664-39-3

: Tetrahydrothiophene 1,1-dioxide 126-33-0

WHMIS Classification : E: Corrosive Material

D1A: Very Toxic Material Causing Immediate and Serious Toxic

Effects

D2A: Very Toxic Material Causing Other Toxic Effects

This product has been classified according to the hazard criteria

of the CPR and the MSDS contains all of the information

required by the CPR.

000000011270

Version 2.5 Revision Date 02/13/2018 Print Date 12/26/2018

SECTION 16. OTHER INFORMATION

	HMIS III	NFPA
Health hazard	: 4*	4
Flammability	: 0	0
Physical Hazard	: 2	
Instability	:	1

* - Chronic health hazard

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

* - Chronic health hazard

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 11/09/2015

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group